# **Century Wheel**












Everyone enjoys a view from above, especially from the top of a Chance Rides Century Wheel. With its 3,000 lights, it also puts on a show for those down below. This classic ride lifts its 15 four- to six-passenger gondolas up to a height of 20 meters.




316.945.6555 sales@chancerides.com chancerides.com

## **Century Wheel**







## **FEATURES**

#### STANDARD FEATURES

- Full 20-meter height provides panoramic view and powerful crowd-drawing ability
- Simultaneous loading of three gondolas per stop for five-stop loading and unloading
- Fifteen 4 to  $\tilde{6}$  passenger gondolas produce the highest hourly capacity of any 20 meter wheel in its class
- More than 3,000 multicolored incandescent lights create a spectacular appearance from both sides, increasing visibility and attracting riders from a distance
- High-back seats and automatic closing doors provide a feeling of security for riders of all ages
- Automatic gondola positioning for loading and unloading reduces operator workload
- Screen displayed diagnostics for ease of ride maintenance OPTIONAL FEATURES
- Rear circle sign with or without logo
- LED Lighting
- Platforms, Ramps and Fencing
- Gondola Canvas Covers

## **SPECIFICATIONS**

SEATING Number of gondolas15
Maximum number of passengers per gondola4 adults
or 6 children
Maximum passenger weight per gondola 680 lbs.
(308 kg)
Maximum total number of passengers60 adults
or 90 children
Maximum total passenger weight 10,200 lbs.
(4,627 kg)
Minimum passenger height
(unaccompanied by adult)
Loading 3 gondolas simultaneously
Maximum unbalance8 adults

PERFORMANCE	
Direction of rotationclockwise/counter	rclockwise
Ride speed	3.5 rpm
Ride duration	2 min.
Maximum wind speed (operating)	
Maximum wind speed (static w/gondolas)	80 mph

MAXIMUM RI	DE WEIGHT	
Empty	44,000	lbs. (19,958 kg)

POWER REQUIREMENTS*	
Total	60 kW
Min./Max. voltage	. 208/230 - 460/480 volt
_	3 phase, 60 Hz

#### **DRIVE\***

Type	variable speed electric
Motor Type	230/460 volt, 3 phase, 60 Hz
Number of motors	4
Horsepower rating	7.5

## LIGHTING\*

Type	LED Ii	ghts
------	--------	------

<sup>\*</sup> All rides can be electrically wired to operate on other specified voltage.

Specifications are effective as of publication date. Because we try to improve every Chance Rides product, these specifications are subject to change without notice. Dimensions given are approximate. For actual dimensions and installation specifications, please refer to Chance Rides foundation drawings. This ride conforms to all applicable ASTM amusement ride standards in effect on the date of manufacture.

